DELIVERY PROGRAM



ROUND RODS

| DIAMETERS (mm) | TOLERANCES (mm) ⁽¹⁾ | | KG/PIECE ⁽²⁾ | ACETRON MD | |
|---|-----------------------------------|------|-------------------------|---------------|--|
| Standard length 3000 mm ⁽³⁾ | | | | | |
| 30 | +0.2 | +1.2 | 3.36 | • | |
| 50 | +0.3 | +2.0 | 9.33 | • | |
| 80 | +0.4 | +3.0 | 23.82 | • | |
| 125 | +0.8 | +3.5 | 57.60 | • | |
| Other standard lengths 1000 mm ⁽³⁾ | | | | | |

- (1): tolerances according to DIN EN 15860 (2): average weights of production (3): tolerances in length -0 / + 3%

PLATES

| THICKNESS (mm) | TOLERANCES (mm) ⁽¹⁾ | KG/PIECE ⁽²⁾ | ACETRON MD | | |
|---|-----------------------------------|-------------------------|---------------|--|--|
| Standard size 610 x 3000 mm ⁽³⁾ | | | | | |
| 20 | +0.3 +1.5 | 59.40 | • | | |
| 40 | +0.5 +2.5 | 117.90 | • | | |
| 80 | +0.5 +5.0 | 234.90 | • | | |
| Other standard sizes 610 x 1000 mm ⁽³⁾ | | | | | |

- (1): tolerances according to DIN EN 15860 (2): average weights of production (3): tolerances in length -0 / \pm 3%