


STANDARD PROFILES

ROLLER CHAIN PROFILES



DOUBLE CHAIN

REFERENCE	STEP	ISO	W	H	A	h	B	Kg/m
LA - 15	3/8"	06 - B2	25	10	5.5	1.5	15.7	0.250
LA - 16	1/2"	08 - B2	35	10	7.5	2.2	21.4	0.360
LA - 17	5/8"	10 - B2	40	10	9.3	2.6	25.9	0.425
LA - 18	5/8"	10 - B2	40	15	9.3	2.6	25.9	0.524
LA - 19	3/4"	12 - B2	45	10	11.3	2.4	30.8	0.480
LA - 20	3/4"	12 - B2	45	15	11.3	2.4	30.8	0.598
LA - 21	1"	16 - B2	48.4	15	16.5	3.5	48.4	0.820
LA - 22	1"	16 - B2	48.4	20	16.5	3.5	48	1.156
LA - 23	1" ¼	20 - B2	55.5	15	19	4.2	55.5	0.930
LA - 24	1" ¼	20 - B2	55.5	20	19	4.2	55.5	1.232
LA - 25	1" ½	24 - B2	73.1	20	24.7	5.5	73.1	1.620
LA - 26	1" ¾	28 - B2	89.7	25	30.1	6.8	89.7	2.490
LA - 27	2"	32 - B2	88.7	30	30.1	7.7	88.7	2.930