


STANDARD PROFILES

ROLLER CHAIN PROFILES



REFERENCE	STEP	ISO	W	V	H	K	h	A	RAIL	Kg/m
LA - 54	3/8"	06 - B1	20	15	15	17	1.5	5.4	C 2010	0.620
LA - 55	1/2"	08 - B1	24	20	9	11	2.2	7.5	C 2405	0.120
LA - 55 - A	1/2"	08 - B1	20	17	15	17	2.2	7.5	C 2010	0.130
LA - 56	5/8"	10 - B1	20	17	15	17	2.6	9.3	C 2010	0.135
LA - 57	3/4"	12 - B1	20	20	15	17	2.4	11.3	C 2812	0.175
LA - 57 - A	3/4"	12 - B1	28	23.5	15	18	2.4	11.3	C 2812	0.289
LA - 58	1"	16 - B1	28	23.5	15	18	3.5	16.5	C 2812	0.297
LA - 59	1" ¼	20 - B1	28	28	15	18	4.3	19.0	C 2812	0.345
LA - 60	1" ½	24 - B1	38	33	25	30	5.5	24.7	C 3818	0.635
LA - 61	1" ¾	28 - B1	38	38	25	30	6.8	30.1	C 3818	0.731
LA - 62 - A	2"	32 - B1	38	38	25	30	7.7	30.1	C 3818	0.710
LA - 62 - B	2"	32 - B1	60	60	25	35	7.7	30.1	C 6020	1.240