


STANDARD PROFILES

ROLLER CHAIN PROFILES



REFERENCE	STEP	ISO	W	H	V	K	I	J	h	d	D	C	RAIL	Kg/m
LA - 96	3/8"	06 - B1	20	17.5	20	21	5.6	8.7	9.9	4	6.6	9.3	C 2010	0.192
LA - 97	1/2"	08 - B1	28	27.5	24	32	7.6	11.5	12.7	5	8.7	12.8	C 2812	0.502
LA - 98	1/2"	10 - B1	28	27.5	24	32	9.3	13.5	14.8	6	10.4	15.4	C 2812	0.452
LA - 99	5/8"	12 - B1	38	34.0	38	43	11.5	15.9	17.5	7.9	12.3	16.9	C 3818	0.729
LA - 100	1"	16 - B1	38	40	38	50	16.5	25.7	27.0	9	16.1	24.4	C 3818	0.620
LA - 101	1" ¼	20 - B1	60	45	60	55	19.0	30.0	32.0	11	19.3	27.5	C 6020	2.640
LA - 102	1" ½	24 - B1	60	55	60	65	25.2	38.2	40.1	16	25.7	36.5	C 6020	2.840
LA - 103	1" ¾	28 - B1	60	70	70	80	30.8	46.9	48.9	17	28.3	41.5	C 6020	4.040
LA - 104	2"	32 - B1	60	70	70	80	30.8	47.3	53.0	19	29.6	44.5	C 6020	4.040