

HIGH-PERFORMANCE PLASTICS **DELIVERY PROGRAM**

ROUND RODS

DIAMETER (mm)	TOLERANCES (mm)		KG/ PIECE [®]	PSU 1000			
Standard length 3000 mm ⁽²⁾							
16	+0.2	+0.9	0.89	0			
20			1.27	•			
25	+0.2	+1.2	2.00	0			
30			2.84	0			
36	+0.2	+1.6	4.08	0			
40			5.01	•			
50	+0.3	+2.0	7.86	0			
Other standard lengths 1000 mm ⁽²⁾⁽³⁾							

Other measures available on request, subject to special conditions (1): average production weights (2): tolerances in length - 0 / + 39% (3): non-standard dimensions for diameters greater than 60mm

PLATES

THICKNESS (mm)	TOLERANCES (mm)		KG/ PIECE®	PSU 1000			
Standard size 625 x 3000 mm ⁽²⁾							
10	+0.2	+0.9	25.71	0			
12	+0.3	+1.5	31.65	0			
15			40.50	0			
16			41.25	0			
20			50.85	0			
25			62.85	0			
30	+0.5	+2.5	76.65	0			
40			100.65	0			
50			124.65	0			
60	+0.5	+3.5	150.15	0			
70			174.15	0			
80	+0.5	+5.0	200.55	0			
Other standard sizes 625 x 1000 mm ⁽²⁾⁽³⁾							

Other measures available on request, subject to special conditions (1): average production weights (2): tolerances in width + 5 / + 25mm, length -0 / + 3% (3): non-standard sizes for thicknesses over 25mm